

EQUIPMENT SPECIFICATIONS

Equipment Type	Dimensions						* Maximum Capacity	Cargo Weight		
	Inside			Outside				Tare Weight	Shipper Loaded	CFS / CFS
	L	W	H	L	W	H				
20' Container, Steel	19' 41/2"	7' 81/2"	7' 9"	20'	8'	8' 6"	1,172 cu.ft.	5,051	38,200	48,060
40' Container, Steel	39' 6"	7' 81/2"	8' 10"	40'	8'	9' 6"	2,693 cu.ft.	8580	43,600	58,620
45' Container, Steel	44' 5 3/4"	7' 8 3/4"	8' 10 1/8"	45'	8'	9' 6"		10,500		
20' Reefer, Electric	17' 8"	7' 6"	7' 1"	20'	8'	8' 6"	938 cu ft	6,480	38,200	47,835
40' Reefer, Electric	37' 9"	7' 4"	8' 3"	40'	8'	9' 6"	2,344 cu ft	10,500	40,800	57,830
20' Open Top	19' 5"	7' 81/2"	7' 91/2"	20'	8'	8' 6"	1,166 cu ft	4,500	38,200	48,105
40' Open Top	39' 5"	7' 8"	7'8.6"	40'	8'	8' 6"	2,669 cu ft	8,500	45,600	58,620
*20' Flatrack	19' 5"	7' 2"	7' 5"	20'	8'	8' 6"		4,400	38,000	49,510
*40' Flatrack	39' 6"	7' 10"	6' 5"	40'	8'	8' 6"		11,000	43,600	57,600

Tropical has a variety of specialized equipment to meet your needs.

Cargo weight includes all packaging and dunnage. It is the gross vehicle weight, less tractor, chassis and container tare weights.

Overweight permits may be available for containers.

CFS/CFS (Container Freight Station to Container Freight Station) means stuffed/unstuffed at the Port.

*20' Flatrack side openings are equivalent to 18'6"

*40' Flatrack side openings are equivalent to 38'3"

* Published measurements reflect *internal* dimensions of the container. Actual loading capacity is based on cargo type and cargo dimensions.